Premium Protection

Waterproofing Sealer for Dark & Light Colored Hardwoods & Thermally Modified Woods

LOW VOC • ECO-FRIENDLY • NON-TOXIC

- Water-based formula
- Prevents water intrusion for 6-10 years
- Inhibits mold, mildew, rot and decay
- Easy clean up with soap and water
- Odorless and non-flammable
- Safe for pets, plants, and people
- Enhances hardwood stability
- Prevents cupping and warping
- Exterior and interior use
- Nanotèchnology formula
- Seals and waterproofs
- For new or refurbished wood.
- 2 coat application, wet on wet
- Amber tint adds UV protection
- Non-film forming, breathable, flexible barrier



APPLICATIONS:

- Decks
- Fences
- Siding

- Outdoor furniture
- Docks
- Shake Roofs
- Actual coverage may vary due to porosity of surface.
 - Railings
 - Timber Framing
 - Play Sets



Semi-Transparent Tint

Enhance Both Light & Dark Hardwoods

The **WISECOAT**® Amber tint enriches the natural splendor and beauty of hardwoods without drastically changing the natural color of the wood.

Always test wood preservative products on scrap wood prior to application. Call DeckWise® at **866-427-2547** to receive a sample to ensure your expected results are acceptable.

WiseCoat® provides long-lasting protection against water intrusion for six (6) years on horizontal surfaces and ten (10) years on vertical surfaces, when used according to the product instructions.

There is no warranty against color fading, whether expressed or implied. In order to maintain color, it is advised to do so with a yearly maintenance plan. Depending on regional climate conditions, additional coats may be applied to restore the preferred natural wood tint color.

EASY APPLICATION! Always mix well before using. Do not apply in rain. For best results, first clean surface with DeckWise* Cleaner and Brightener.



1. CLEAN, RINSE, & LET DRY



2. APPLY 2 COATS WET OVER WET




3. BACKBRUSH ANY PUDDLES

For complete Use & Care instructions go to: www.deckwise.com

PROTECT YOUR DECK WITH IPE SEAL®

Ipe Seal* is a wax emulsion sealer proven to increase the structural integrity of hardwood decking. Once applied to freshly cut, exposed wood end grain, Ipe Seal* creates a bond that extends the life of each deck board while also preventing splits (end checking) and unsightly cracks.







1 quart per 500 sq ft. of deck



Phone: 941-896-9851 • Toll free: 866-427-2547

Email: info@DeckWise.com • www.DeckWise.com