



Penofin[®] -RenewAll

Unique Elastomeric Resin System
Premium flexibility and adhesion.

Locks Down Splinters
Smooth's rough surfaces and fills cracks to 1/4"

Creates a Finely Textured Surface
Barefoot friendly, skid resistant

Platinum Level UV Protection
Durability against the elements

Water Proof Protection
Creates a unique breathable surface

Can Be Used On Wood or Concrete

Meets ADA & OSHA Slip Resistance Standards
For decks, external ramps, stairs, concrete surfaces, swimming pool sides and other areas that require a slip resistant surface.





Performance Coatings Inc.
Ukiah, California
Penofin Pure Life Pure Style
Product Data Sheet

Penofin® RenewAll

Brings old, worn wood and concrete back to life. The thick elastomeric formula will fill cracks up to 1/4" and correct unsightly splinters creating an attractive non-slip, non-skid and dirt resistant surface. Penofin RenewAll is for horizontal surfaces and will add years to the life of any deck, patio or porch.

Performance Features: Barefoot Friendly Surface, Low Odor, Low VOC
Extends The Life of Wood and Masonry Surfaces.

Penofin® RenewAll Applications:
Decks, Patios, Side Walks, Brick and Stone.

Meets ADA & OSHA slip resistance standards for decks, external ramps, stairs, concrete surfaces, swimming pool sides and other areas that require a slip resistant surface.

TECHNICAL DATA:

VOC: 50 g/l
Resin Type: Elastomeric/Acrylic Latex blend
Density: 10.99 (lbs/gallon)
Viscosity Krebs: 140 – 145 KU
Solids (% by weight): 65%
Solids (% by volume): 53%
PH: 8.5 – 9.5
Gloss @ 60 degrees: <4 degrees
Sheen: Flat
Tint Base: Deep
Pre-Tinted Colors: Adobe, Pewter, Sea Ranch, Seal, Suede, Terra Cotta

Installation Temperature: 50— 80 degrees Fahrenheit. Do not apply in direct sunlight or if the temperature may fall below 50 F° within 48hours.
Dry to Touch: 4-6 hours then apply another coat, serviceable in 24 hours
Full Cure: 72 hours
Coverage: Approximately 75 sq.ft per gallon. Requires 2-coats.

SURFACE PREPARATION:

Remove any loose splinters or fibers and replace rotting or severely damaged boards. Prepare the surface with Penofin Pro-Tech Cleaner. Fill in cracks larger than 1/4" with exterior wood filler. New Concrete should cure 30 days before application. Then treat with Penofin Pro-Tech Brightener. **Not recommended for driveways or garage floors.**

APPLICATION:

Shake and stir thoroughly before and during use. Blend multiple containers together to ensure uniformity of color. Product can be applied with a brush, roller or air assisted sprayer. Fill cracks and apply to rough areas first, then apply a thick even coat lengthwise along the boards. Allow to dry 4-6 hours and then apply a second coat. Do not apply over wet or damp surfaces or when rain is imminent. Do not intermix with any other products or thin. Protect containers from freezing. For exterior use only

May cause eye and skin irritation. Use only with adequate ventilation. Avoid breathing vapors, spray mist or sanding dust. If you experience eye watering, headache or dizziness, wear an appropriate properly fitted respirator (Niosh approved) during and after application. Wash thoroughly after handling. Close container after each use. DO NOT TAKE INTERNALLY.

WARNING: This product contains a chemical known to the State of California to cause cancer.

CLEAN-UP:

Clean brushes and equipment with soap and water. Dispose of empty cans or unused portion in accordance with local, state and federal regulations.

Please visit our website www.penofin.com for more application & wood care tips, or call our live customer service line at:

**1-800-PENOFIN Monday—Friday
7:00am-4:00pm (PST), or email us at
mail@penofin.com.**