

Introducing
GEN II



**THE
ULTIMATE
FASTENERS**

EXTERIOR

STRUCTURAL

AXIS™




Horizon Curve Head

A slight curvature of the head for elegant, professional results. The Finish Ring underneath the head also provides a better finish by cutting the top fibers in the wood for an extra step in countersinking.



Turbine Ribs

The Turbine Ribs cut quickly into the wood, leaving a professional, clean finish with maximum wood contact. The cup shaped countersinking head provides increased holding power and reduced risk of splitting.



Twin Blade Knurls

This set of knurls cuts fast to dramatically reduce friction and heat on the shank, while reducing load on the drill. They also provide better performance by removing debris faster than a standard fastener's knurl.



Fast Start Tip

With the sharp threads all the way to the tip, the fastener has an immediate grip for a fast start. The inset thread cut drastically reduces splitting effect and minimizes the driving torque needed to engage the wood.

The Advanced, General Purpose Wood Screw with corrosion protection coating is for typical high-corrosive exterior and interior environments
Great for any size job or project.



Available in 1lb, 5lb and 1/4 Keg
All Packaging Includes Free Bit!

WWW.SCREW-PRODUCTS.COM

9401 Bujacich Rd. Bldg 1B, Gig Harbor, WA 98332
Toll-Free 1-877-844-8880

THE ULTIMATE FASTENERS

FOLLOW US



#SCREWPRODUCTSINC

Oct 14, 2019



THE ULTIMATE FASTENERS

EXTERIOR

STRUCTURAL

The AXIS™ Wood Screw is designed to take wood screws to an entire new level. Every facet has been evaluated and improved (patents pending). Our extra sharp Fast Start Tip saves you time onsite and the Twin Blade Knurls outperform the competitors. The Turbine Ribbs ensure an incredibly clean finish. Its cup shaped countersinking head, provides unparalleled holding power and less risk of splitting the wood. The Horizon Curve Head has been architecturally engineered to leave an elegant finish.



TYPICAL EXTERIOR USE

ZYTEC™XT: for general outdoor use. Compatible with most above ground pressure treated lumber. For ground contact treated lumber, areas within one mile of saltwater, near swimming pools, exposure to corrosive chemicals, or other areas where corrosion is more likely to occur, use proper grade Stainless Steel.

Common Applications

- General indoor and outdoor jobs
- Decking, railing and fencing
- Roofing and siding
- Construction, remodeling and repair
- Framing, windows and doors
- Trim
- Cabinetry
- And much more!

Sizes Available: #8 x 3/4" to #14 x 8"

General Info					
Type of Screw	General Purpose Wood				
Material	Coated Carbon Steel				
Coating	ZYTEC™ XT				
Head Style	Countersinking Star Drive				
Point Type	17				
Construction	#8	#9	#10	#14	
Head diameter (inch)	.331	.370	.409	.488	
Minor thread diameter	.106	.122	.136	.152	
Major thread diameter	.165	.183	.211	.246	
Shaft diameter	.122	.136	.154	.173	
Drive Size	TX20	TX20	TX20	TX30	
Product Range		Approx Count per 1lb			
Length	Thread	#8	#9	#10	
3/4"	5/8"	326			
1"	3/4"	256	196		
1-1/4"	7/8"	219	164		
1-1/2"	1"	183	141		
1-3/4"	1-1/8"	162			
2"	1-1/4"	144	112	85	
2-1/2"	1-1/2"		90	69	
2-3/4"	1-1/2"		78		
3"	1-1/2"		78	59	
3-1/2"	2"			51	
4"	2"			45	
5"	2-1/2"			36	28
6"	2-1/2"			30	24
7"					20
8"					18



WWW.SCREW-PRODUCTS.COM

9401 Bujacich Rd. Bldg 1B, Gig Harbor, WA 98332
Toll-Free 1-877-844-8880

THE ULTIMATE FASTENERS

FOLLOW US



#SCREWPRODUCTSINC