Introducing CEN II



THE ULTIMATE FASTENERS

EXTERIOR

STRUCTURAL

Horizon Curve[™]

A slight curvature of the head for elegant, professional, architectural results. The Finish Ring underneath the head also provides a better finish by cutting the top fibers in the wood for an extra step in countersinking.

Turbine Ribs™

(patent pending) Turbine Ribs cut quickly into the wood, leaving a professional, clean finish with maximum wood contact. The cup shaped, countersinking head provides increased holding power and reduced risk of splitting.

Twin Blades™

(patent pending) This set of knurls cuts fast to dramatically reduce friction and heat on the shank, while reducing load on the drill. They also provide better performance by removing debris faster than a standard fastener's knurl.

Fast Start Tip

With sharp threads all the way to the tip, the fastener has an immediate grip for a fast start. The inset thread cut drastically reduces the splitting effect and minimizes the driving torque needed to engage the wood.

This advanced, General Purpose Structural Wood Screw with ZYTEC™XT corrosion protection coating is for typical high-corrosive exterior and interior environments. Use them on any size job or project from framing to small wood working!



Available in 1lb, 5lb and 1/4 Keg All Packaging Includes Drive Bit!

WWW.SCREW-PRODUCTS.COM

Gig Harbor, WA 98332 Toll-Free 1-877-844-8880 THE ULTIMATE FASTENERS





The AXIS™ Structural Wood Screw is the next step in fastener design. Every facet has been evaluated and improved (patents pending). Our extra sharp Fast Start Tip saves you time onsite and the Twin Blades outperform the competitor's knurls. The Turbine Ribs ensure an incredibly clean finish. Its cup shaped, countersinking head, provides unparalleled holding power and less risk of splitting the wood. The Horizon Curve Head has been architecturally engineered to leave an elegant finish.













TYPICAL EXTERIOR USE

ZYTEC™XT Coating: For general outdoor use. Compatible with most above ground pressure treated lumber. For ground contact treated lumber, areas within one mile of saltwater, near swimming pools, exposure to corrosive chemicals, or other areas where corrosion is more like to occur, use proper grade **Stainless Steel.** Always follow timber manufacturer's recommendations for fasteners.

Common Applications

- Commercial & residential
- General indoor and outdoor jobs
- Decking, railing and fencing
- Roofing and siding
- Construction, remodeling and repair
- Framing, windows and doors
- Trim & Cabinetry
- And much more!

Sizes Available: #8 x 3/4" to #14 x 8"

General I	nfo					
Type of Screw		General Purpose Structural Wood				
Material		Heat Treated, Hardened Steel				
Coating		ZYTEC™ XT				
Head Style		Countersinking TX20/30 Star Drive				
Point Type		Modified Type 17				
Constr		#8	#9	#10	#14	
Head diameter (inch)			.323	.350	.386	.488
Minor thread diameter			.106	.122	.136	.152
Major thread diameter			.165	.183	.211	.246
Shaft diameter			.122	.136	.154	.173
Drive Size			TX20	TX20	TX20	TX30
Product Range			Approx Count per 1lb			
Length	Thre	ead	#8	#9	#10	#14
3/4"	5/8"		326			
1"	3/4"		256	196		
1-1/4"	7/8"		219	164		
1-1/2"	1"		183	141		
1-3/4"	1-1/8"		162			
2"	1-1/4"		144	112	85	
2-1/2"	1-1/2"			90	69	
2-3/4"	1-1/2"			78		
3"	1-1/	/2"		78	59	
3-1/2"	2"				51	
4"	2"				45	
5"	2-1/2"				36	28
6"	2-1/2"				30	24
7"						20
8"						18



Gig Harbor, WA 98332 Toll-Free 1-877-844-8880