



THE ULTIMATE FASTENERS

INTERIOR

STRUCTURAL



Horizon Curve™

A slight curvature of the head for elegant, professional, architectural results. The Finish Ring underneath the head also provides a better finish by cutting the top fibers in the wood for an extra step in countersinking.



Turbine Ribs™

(patent pending) Turbine Ribs cut quickly into the wood, leaving a professional, clean finish with maximum wood contact. The cup shaped, countersinking head provides increased holding power and reduced risk of splitting.



Twin Blades™

(patent pending) This set of knurls cuts fast to dramatically reduce friction and heat on the shank, while reducing load on the drill. They also provide better performance by removing debris faster than a standard fastener's knurl.



Fast Start Tip

With sharp threads all the way to the tip, the fastener has an immediate grip for a fast start. The inset thread cut drastically reduces the splitting effect and minimizes the driving torque needed to engage the wood.

This advanced, General Purpose Structural Wood Screw is for typical interior, medium-corrosive environments. Use them on any size job or project from framing to small wood working!



Available in 1lb, 5lb and 1/4 Keg All Packaging Includes Drive Bit!

WWW.SCREW-PRODUCTS.COM

Gig Harbor, WA 98332 Toll-Free 1-877-844-8880 THE ULTIMATE FASTENERS





The AXIS™ Structural Wood Screw is the next step in fastener design. Every facet has been evaluated and improved (patents pending). Our extra sharp Fast Start Tip saves you time onsite and the Twin Blades outperform the competitor's knurls. The Turbine Ribs ensure an incredibly clean finish. Its cup shaped, countersinking head, provides unparalleled holding power and less risk of splitting the wood. The Horizon Curve Head has been architecturally engineered to leave an elegant finish.











TYPICAL INTERIOR USE

ZYTEC™+ Coating: Typical heated, dry room environments with clean air (low or no condensation/minimal outdoor exposure) such as homes, shops, offices, schools, hotels, etc. Environmentally friendlier than any Yellow Zinc that contains Chromium 6. Always follow timber manufacturer's recommendations for fasteners.

Common Applications

- Commercial & residential
- General indoor jobs
- Remodeling and repair
- Interior framing
- Trim work & Cabinetry
- Windows and doors
- Post and beam & much more!

Sizes Available: #8 x 1" to #10 x 6"

General I	nto				
Type of Screw		General Purpose Structural Wood			
Material		Heat Treated, Hardened Steel			
Coating		ZYTEC™ +			
Head Style		Countersinking TX20 Star Drive			
Point Type		Modified Type 17			
Construction			#8	#9	#10
Head diameter (inch)			0.323	0.350	0.386
Minor thread diameter			0.106	0.122	0.136
Major thread diameter			0.165	0.183	0.211
Shaft diameter			0.122	0.136	0.154
Drive Size			TX20	TX20	TX20
Product Range		,	Approx Count per 1lb		
Length	Thread		#8	#9	#10
1"	3/4"		253		
1-1/4"	7/8	8"	214		
1-1/4" 1-1/2"	7/8 1				111
		II	214		111
1-1/2"	1	/8"	214 181	112	111
1-1/2" 1-3/4"	1-1/	" /8" /4"	214 181 159	112 92	
1-1/2" 1-3/4" 2"	1 1-1/ 1-1/	" /8" /4" /2"	214 181 159 146		85
1-1/2" 1-3/4" 2" 2-1/2"	1-1/ 1-1/ 1-1/	" /8" /4" /2"	214 181 159 146	92	85
1-1/2" 1-3/4" 2" 2-1/2" 2-3/4"	1 1-1, 1-1, 1-1, 1-1,	" /8" /4" /2" /2"	214 181 159 146	92 83	85 70
1-1/2" 1-3/4" 2" 2-1/2" 2-3/4" 3"	1-1/ 1-1/ 1-1/ 1-1/ 1-1/	/8" /4" /2" /2" /2"	214 181 159 146	92 83	85 70 59
1-1/2" 1-3/4" 2" 2-1/2" 2-3/4" 3" 3-1/2"	1 1-1, 1-1, 1-1, 1-1, 1-1, 2	/8" /4" /2" /2" /2"	214 181 159 146	92 83	85 70 59 51

